

Siechem UL 3122 ATC Silicone Rubber Insulated and Lacquered Braided 200°C 300 Vac Cable
Application

- ✓ Internal wiring of meters, panels, electrical and electronic equipment.
- ✓ Appliance wiring

Product Construction


- ✓ Conductor : Annealed Tinned Solid / Stranded Copper Conductor
- ✓ Insulation : Silicone Rubber
- ✓ Covering : Lacquered Braid

Technical Data

- ✓ Operating Temperature : - 40°C to + 200°C
- ✓ Voltage : 300 Vac
- ✓ Test method : UL 758

Features

- ✓ RoHS compliant
- ✓ High temperature resistance
- ✓ Halogen free

2D View


	ISO 9001	ISO 14001	OHSAS 18001	AS 9100
AS 45001		ALSTOM		

Part Number	Conductor Size	No. of Strands / Strand dia	Nominal Wall Thickness	Nominal Overall Diameter	Max. Conductor Resistance at 20°C	Weight (Approx.)
	AWG	Nos/mm	mm	mm	Ω/km	Kg/Km
A18285XX	26	1/0.407	0.38	1.9	143	5
A18384XX	24	7/0.193	0.38	2.0	94.2	6
A18383XX	22	7/0.254	0.38	2.2	59.4	8
A18382XX	20	10/0.255	0.38	2.4	37.2	9
A18381XX	18	16/0.255	0.38	2.6	23.4	13
A18380XX	16	26/0.255	0.38	2.9	14.7	18

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	


www.siechem.com